


# xerxes

Stehleuchte | Floor lamp | Lampadaire | Lampada a stelo



**A++** **A**




220-240V IP20  $R_f > 90$  UGR < 13 up to L80/50.000h MacAdam 3



**LED**  
3000 K, 4000 K, dynamic white  
up to 113 lm/W  
 $R_f > 90$ , UGR < 13, MacAdam 3  
IEC 62471: Blue light hazard: RG ≤ 1  
Lifetime up to L80 / 50.000 h

**Optic**  
direct/indirect  
microprism

**Options**  
 $R_f > 80$

**Housing**  
powder coated  
silver   
white   
black 

## xerxes

T59T061-1 C2 2 X 3 M

### 1 Gehäusefarbe | Housing colour | Couleur du luminaire | Colore profilo

silber   silver   argent   argento	SISI
weiß   white   blanc   bianco	WSWS
schwarz   black   noir   nero	SWSW

### 2 Farbtemperatur | Colour temperature | Température de couleur | Temperatura colore

LF930, 3000 K	930
LF940, 4000 K	940
2700 - 6500 K dynamic white (no sensor)	HCL

### 3 Dimming & sensors

dimnable, no sensor	3
daylight and motion sensor	7

Beispiel | Example | Exemple | Esempio

white, 4000 K, Sensor

**T59T061-WSWSC2940X7M**

	3000 K	4000 K	dynamic white
Luminous Flux (lm)	8230 lm	8670 lm	7630 lm
System Power (W)	78 W	78 W	67 W

Weight (kg) 13,7 kg

