

### Item

S44F006-BCSIC1940H33  
anto+ recessed frameless silver 64x44

### General

LED HO 4000K 6,7W 354lm 30° DALI 02 Spots  
housing silver RAL9006 matte  
anti-glare cone silver glossy, anti-glare attachment  
chrome matte  
mounting frame

### Illuminant

LED HO  
EEC A++ - A  
Colour rendering index (CRI) > 90  
Blue light hazard RG1 IEC 62471  
MacAdam 3



### Dimension

LxWxH: 64x44x043mm  
Cut-out LxWxD: 73x52x170mm

### Surface/Colour

profile: aluminium, anti-glare attachment:  
Polycarbonate

### Lens

Lens technology  
Radiation angle: 30°

### Protection rating

IP20 / Protection class I

### Connection

230V 50/60Hz  
incl. converter DALI

### Weight

0,3 kg



### Product-Information

High-end frameless recessed profile luminaire, casing constructed out of aluminium, anti-glare attachment made of polycarbonate. Luminaire consists of 2 light points with efficient high-power LEDs in the colour combination: anti-glare cone silver glossy, anti-glare attachment chrome matte, housing silver RAL9006 matte. Unique lens technology and recessed optics. Direct light emission, light geometry symmetric with an emittance angle 'Medium' of 30°. Colour rendering index (CRI) > 90, with an efficiency of 53 lm per W producing a luminous flux of 354 lm with 6,7 W, colour temperature of 4000 K. Including a dimmable DALI converter, small colour tolerance MacAdam 3, energy efficiency class according to delegated Commission Regulation (EU) No. 518/2014: A++ - A. Rated lifetime of minimum 60.000 h [according to EU decree No. 1194/2012], Ingress Protection IP20, Protection Class I. Electrical connection through 5 used pins. Including endcaps mounting frame. Dimensions LxWxH: 64x44x043 mm, Cut-out LxWxD: 73x52x170 mm, Weight: 0,3 kg