

Item

S44F024-WBSWC1HCLX33
anto+ recessed frameless black 244x44 DT6

General

LED HCL 2700-6500K 11,5W 656lm 30° DALI 08 Spots
housing black RAL9005 matte
anti-glare cone white matte, anti-glare attachment
silver glossy
mounting frame

Illuminant

LED HCL
EEC A++ - A
Colour rendering index (CRI) > 90
Blue light hazard RG1 IEC 62471
MacAdam 3

Dimension

LxWxH: 244x44x043mm
Cut-out LxWxD: 253x52x080mm

Surface/Colour

profile: aluminium, anti-glare attachment:
Polycarbonate

Lens

Lens technology
Radiation angle: 30°

Protection rating


IP20 / Protection class I

Connection

230V 50/60Hz
incl. converter DALI

Weight

0,8 kg



Product-Information

High-end frameless recessed profile luminaire, casing constructed out of aluminium, anti-glare attachment made of polycarbonate. Luminaire consists of 8 light points with efficient high-power LEDs in the colour combination: anti-glare cone white matte, anti-glare attachment silver glossy, housing black RAL9005 matte. Unique lens technology and recessed optics. Direct light emission, light geometry symmetric with an emittance angle 'Medium' of 30°. Colour rendering index (CRI) > 90, with an efficiency of 56 lm per W producing a luminous flux of minimum 656 lm with 11,5 W, colour temperature in tunable white of 2700-6500 K. Including a dimmable DALI converter, small colour tolerance MacAdam 3, energy efficiency class according to delegated Commission Regulation (EU) No. 518/2014: A++ - A. Rated lifetime of minimum 60.000 h [according to EU decree No. 1194/2012], Ingress Protection IP20, Protection Class I. Electrical connection through 7 used pins. Including endcaps mounting frame. Dimensions LxWxH: 244x44x043 mm, Cut-out LxWxD: 253x52x080 mm, Weight: 0,8 kg