

### Item

T59T061-SISIC2930X3M  
xerxes Floor lamp silver

### General

LED 3000K 78W 8230lm  
3000mm black supply cable with two-pin earthed plug

### Illuminant

LED  
EEI A++ -A  
Colour rendering index (CRI) > 90  
MacAdam 3  
UGR < 13

### Dimension

LxWxH: 615x325x046/1945mm

### Surface/Colour

Material: anodised aluminium / steel sheet  
powder-coated with fine matte finish  
Surface silver

### Lens

PMMA microprismatic  
PMMA clear (id)

### Protection rating




IP20 / Protection class I

### Connection

220-240/AC  
incl. converter push-button dimming

### Weight

13,7 kg



### Product-Information

High-class LED floor lamp designed for direct-indirect light emission, in a flat, rectangular design made of extruded aluminium fine structure powder coating in matte silver. Foot plate made of steel sheet. Direct-indirect emission of light in a 1:3 proportion. Inclined LED boards on the indirect side for optimal lighting of working space. Direct light emission through a light guiding plate (LGP) with a PMMA microprism for a homogeneous light emission and reduced glare with a Unified Glare Rating (UGR) < 13 with an efficiency of 106 lm per W. Indirect light emission through a clear PMMA diffuser. Luminaire equipped with the latest generation of LED boards with an Colour Rendering Index (CRI) > 80, a small colour tolerance MacAdam 3, Rated lifetime of minimum 50.000 h [according to EU decree No. 1194/2012], Energy Efficiency Index (EEI) A++ -A. Ingress Protection IP20, Protection Class I. Colour temperature of 3000 K. Converter included, dimmable with on / off push button in the range 1 % to 100 %. Dimensions: Luminaire 615x325x46 mm (LxWxH), foot plate 300x500x4 mm (LxWxH), Lamp total height 1950 mm. Weight: 13,7 kg