

#### Item

S44A054-PYSWC1940M14  
anto+ surface black 547x44

#### General

LED MO 4000K 29W 1800lm 45° 18 Spots  
housing black RAL9005 matte  
anti-glare cone silver matte, anti-glare attachment  
grey matte  
for recessed version 2 mounting brackets required

#### Illuminant

LED MO  
EEC A++ - A  
Colour rendering index (CRI) > 90  
Blue light hazard RG1 IEC 62471  
MacAdam 3

#### Dimension

LxWxH: 547x44x082mm  
Cut-out LxWxD: 552x49x100mm

#### Surface/Colour

profile: aluminium, anti-glare attachment:  
Polycarbonate

#### Lens

Lens technology  
Radiation angle: 45°

#### Protection rating



IP20 / Protection class I

#### Connection

230V 50/60Hz  
incl. converter

#### Weight

1.3 kg



#### Product-Information

High-end surface-mounted profile luminaire, casing constructed out of aluminium, anti-glare attachment made of polycarbonate. Luminaire consists of 18 light points with efficient high-power LEDs in the colour combination: anti-glare cone silver matte, anti-glare attachment grey matte, housing black RAL9005 matte. Unique lens technology and recessed optics. Direct light emission, light geometry symmetric with an emittance angle 'Wide Flood' of 45°. Colour rendering index (CRI) > 90, with an efficiency of 62 lm per W producing a luminous flux of 1800 lm with 29 W, colour temperature of 4000 K. Including a converter, small colour tolerance MacAdam 3, energy efficiency class according to delegated Commission Regulation (EU) No. 518/2014: A++ - A. Rated lifetime of minimum 60.000 h [according to EU decree No. 1194/2012], Ingress Protection IP20, Protection Class I. Electrical connection through 3 used pins. Also suitable for semi-recessed mounting using separately available components (mounting brackets). Including endcaps, for recessed version 2 mounting brackets required. Dimensions LxWxH: 547x44x082 mm, Cut-out for recessed mounting LxWxD: 552x49x100 mm, Weight: 1.3 kg