

Item

S44F024-RYWSC1940H1A
anto+ recessed frameless white asy 244x44

General


LED HO 4000K 18W 1036lm 08 Spots
housing white RAL9016 matte
anti-glare cone copper matte, anti-glare attachment
grey matte
mounting frame

Illuminant

LED HO
EEC A++ - A
Colour rendering index (CRI) > 90
Blue light hazard RG1 IEC 62471
MacAdam 3

Dimension

LxWxH: 244x44x043mm
Cut-out LxWxD: 253x52x080mm



Surface/Colour

profile: aluminium, anti-glare attachment:
Polycarbonate

Lens

Lens technology asymmetric

Protection rating


IP20 / Protection class I

Connection

230V 50/60Hz
incl. converter

Weight

0,6 kg



Product-Information

High-end frameless recessed profile luminaire, casing constructed out of aluminium, anti-glare attachment made of polycarbonate. Luminaire consists of 8 light points with efficient high-power LEDs in the colour combination: anti-glare cone copper matte, anti-glare attachment grey matte, housing white RAL9016 matte. Unique lens technology and recessed optics. Direct light emission, light geometry asymmetric. Colour rendering index (CRI) > 90, with an efficiency of 58 lm per W producing a luminous flux of 1036 lm with 18 W, colour temperature of 4000 K. Including a converter, small colour tolerance MacAdam 3, energy efficiency class according to delegated Commission Regulation (EU) No. 518/2014: A++ - A. Rated lifetime of minimum 60.000 h [according to EU decree No. 1194/2012], Ingress Protection IP20, Protection Class I. Electrical connection through 3 used pins. Including endcaps mounting frame. Dimensions LxWxH: 244x44x043 mm, Cut-out LxWxD: 253x52x080 mm, Weight: 0,6 kg