

### Item

S44F006-BPWSC1940H11  
anto+ recessed frameless white 64x44

### General

LED HO 4000K 5,8W 385lm 15° 02 Spots  
housing white RAL9016 matte  
anti-glare cone silver glossy, anti-glare attachment  
silver matte  
mounting frame

### Illuminant

LED HO  
EEC A++ - A  
Colour rendering index (CRI) > 90  
Blue light hazard RG1 IEC 62471  
MacAdam 3



### Dimension

LxWxH: 64x44x043mm  
Cut-out LxWxD: 73x52x080mm

### Surface/Colour

profile: aluminium, anti-glare attachment:  
Polycarbonate

### Lens

Lens technology  
Radiation angle: 15°

### Protection rating


IP20 / Protection class I

### Connection

230V 50/60Hz  
incl. converter

### Weight

0,2 kg



### Product-Information

High-end frameless recessed profile luminaire, casing constructed out of aluminium, anti-glare attachment made of polycarbonate. Luminaire consists of 2 light points with efficient high-power LEDs in the colour combination: anti-glare cone silver glossy, anti-glare attachment silver matte, housing white RAL9016 matte. Unique lens technology and recessed optics. Direct light emission, light geometry symmetric with an emittance angle 'Spot' of 15°. Colour rendering index (CRI) > 90, with an efficiency of 66 lm per W producing a luminous flux of 385 lm with 5,8 W, colour temperature of 4000 K. Including a converter, small colour tolerance MacAdam 3, energy efficiency class according to delegated Commission Regulation (EU) No. 518/2014: A++ - A. Rated lifetime of minimum 60.000 h [according to EU decree No. 1194/2012], Ingress Protection IP20, Protection Class I. Electrical connection through 3 used pins. Including endcaps mounting frame. Dimensions LxWxH: 64x44x043 mm, Cut-out LxWxD: 73x52x080 mm, Weight: 0,2 kg