

### Item

S44E037-DYSIC1930H3A  
anto+ recessed frame silver asy 376x56

### General

LED HO 3000K 26W 1509lm DALI 12 Spots  
housing silver RAL9006 matte  
anti-glare cone gold matte, anti-glare attachment  
grey matte  
2 mounting brackets

### Illuminant

LED HO  
EEC A++ - A  
Colour rendering index (CRI) > 90  
Blue light hazard RG1 IEC 62471  
MacAdam 3

### Dimension

LxWxH: 376x56x043mm  
Cut-out LxWxD: 370x49x080mm

### Surface/Colour

profile: aluminium, anti-glare attachment:  
Polycarbonate

### Lens

Lens technology asymmetric

### Protection rating


IP20 / Protection class I

### Connection

230V 50/60Hz  
incl. converter DALI

### Weight

0,7 kg



### Product-Information

High-end recessed profile luminaire, casing constructed out of aluminium, anti-glare attachment made of polycarbonate. Luminaire consists of 12 light points with efficient high-power LEDs in the colour combination: anti-glare cone gold matte, anti-glare attachment grey matte, housing silver RAL9006 matte. Unique lens technology and recessed optics. Direct light emission, light geometry asymmetric. Colour rendering index (CRI) > 90, with an efficiency of 57 lm per W producing a luminous flux of 1509 lm with 26 W, colour temperature of 3000 K. Including a dimmable DALI converter, small colour tolerance MacAdam 3, energy efficiency class according to delegated Commission Regulation (EU) No. 518/2014: A++ - A. Rated lifetime of minimum 60.000 h [according to EU decree No. 1194/2012], Ingress Protection IP20, Protection Class I. Electrical connection through 5 used pins. Including endcaps and 2 mounting brackets or installation spring(s). Dimensions LxWxH: 376x56x043 mm, Cut-out LxWxD: 370x49x080 mm, Weight: 0,7 kg