

Item

S44F006-CGWSC1930L1A
anto+ recessed frameless white asy 64x44

General

LED LO 3000K 3W 158lm 02 Spots
housing white RAL9016 matte
anti-glare cone chrome matte, anti-glare attachment
gold glossy
mounting frame

Illuminant

LED LO
EEC A++ - A
Colour rendering index (CRI) > 90
Blue light hazard RG1 IEC 62471
MacAdam 3



Dimension

LxWxH: 64x44x043mm
Cut-out LxWxD: 73x52x080mm

Surface/Colour

profile: aluminium, anti-glare attachment:
Polycarbonate

Lens

Lens technology asymmetric

Protection rating

IP20 / Protection class I

Connection

230V 50/60Hz
incl. converter

Weight

0,2 kg



Product-Information

High-end frameless recessed profile luminaire, casing constructed out of aluminium, anti-glare attachment made of polycarbonate. Luminaire consists of 2 light points with efficient high-power LEDs in the colour combination: anti-glare cone chrome matte, anti-glare attachment gold glossy, housing white RAL9016 matte. Unique lens technology and recessed optics. Direct light emission, light geometry asymmetric. Colour rendering index (CRI) > 90, with an efficiency of 53 lm per W producing a luminous flux of 158 lm with 3 W, colour temperature of 3000 K. Including a converter, small colour tolerance MacAdam 3, energy efficiency class according to delegated Commission Regulation (EU) No. 518/2014: A++ - A. Rated lifetime of minimum 60.000 h [according to EU decree No. 1194/2012], Ingress Protection IP20, Protection Class I. Electrical connection through 3 used pins. Including endcaps mounting frame. Dimensions LxWxH: 64x44x043 mm, Cut-out LxWxD: 73x52x080 mm, Weight: 0,2 kg